



Innlights^{TC}
 Rent & Buy LED Displays

InnScreen B8

[PIXEL PITCH 8,9 mm] Indoor / Outdoor

// Floor and Wall Installation

High stable with a payload of **2000 kg/m²**.
 Protection cover and adjustable base support.

For fashion shows, car-shows and show rooms.



FACTS [m²]

BRIGHTNESS [cd/m ²]	3.000
WEIGHT [kg/m ²]	54
RESOLUTION [pixel/m ²]	112 x 112
CABINETS PER m ²	4
WATTAGE MAX./AVG. [W/m ²]	800 / 280

RENTAL



Innlights^{TC}

Rent & Buy LED Displays

InnScreen B8

PHYSICAL FACTS

PIXEL PITCH [mm]	8,9
BRIGHTNESS [cd/m ²]	3.000
PROTECTION LEVEL	IP 65
CABINET SIZE [mm]	500 x 500 x 82
CABINET WEIGHT [kg]	13,6
CABINET RESOLUTION [px]	56 x 56
PIXEL DENSITY [px/m ²]	12.544
CABINET MATERIAL	Aluminum

ACCESSORIES

CABINET CASE SIZE (LxWxH) [mm]	75 x 58 x 73
CABINET CASE WEIGHT (full) [kg]	125
CABINETS PER CASE	6
m ² PER CASE	1,50
HANGING BRACKETS	Single / Double

INNLIGHTS STANDARDS

White Face LED (Outdoor Series)
Professional MuNu/Connex Power Cables
Neutrik Connectors (powerCON NAC ₃)
Professional Image Processing / Video Direction
High Class Connex Power Distributor
Certificates: CE (EMV), RoHs

OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	120 / 120
REFRESH RATE [Hz]	1.200
IC DRIVER	MBI 5041
DRIVING METHOD [scan mode]	1 / 16
LED TYPE	SMD 3535
LED CHIP	Epistar (R) / Silan (G,B)
LED ENCAPSULATION	NationStar
GREY LEVEL [bit]	14
VIDEO PROCESSING	Linsn

POWER SUPPLY

INPUT VOLTAGE [V]	110 - 240
WATTAGE MAX./AVG. [W /Cabinet]	200 / 70
WATTAGE MAX./AVG. [W /m ²]	800 / 280
CABINETS PER 16 A PHASE	3

ENVIRONMENT

OPERATION HUMIDITY [RH]	10% - 90%
WORKING TEMP. MIN./MAX. [°C]	-30 / +50

RENTAL