



# Innlights<sup>TC</sup>

Rent & Buy LED Displays

## InnScreen F6

[ PIXEL PITCH 6,66 mm ] Outdoor

// Fixed-Installation Outdoor

All weather & UV resistance  
combined with high brightness.

Sealed cabinet design and full front access  
precisely define the F-Series as the prime  
selection for permanent outdoor installations.

2 cabinet sizes.

### FACTS [m<sup>2</sup>]

BRIGHTNESS [cd/m <sup>2</sup> ]	6.000
WEIGHT [kg/m <sup>2</sup> ]	23 - 33
RESOLUTION [pixel/m <sup>2</sup> ]	150 x 150
WATTAGE MAX./AVG. [W/m <sup>2</sup> ]	742 / 248



SALES



# Innlights<sup>TC</sup>

Rent & Buy LED Displays

## InnScreen F6 // Customized

### PHYSICAL FACTS

PIXEL PITCH [mm]	6,66
BRIGHTNESS [cd/m <sup>2</sup> ]	6.000
PROTECTION LEVEL [Front/Back]	IP 65 / IP 54
CABINET MATERIAL	Aluminum sheet

<b>CABINET SIZE [mm]</b>	<b>800 x 800 x 85</b>
CABINET RESOLUTION [px]	120 x 120
CABINET WEIGHT [kg]	18

<b>CABINET SIZE [mm]</b>	<b>1.200 x 1.200 x 85</b>
CABINET RESOLUTION [px]	180 x 180
CABINET WEIGHT [kg]	40

### INNLIGHTS CUSTOMIZED

IC Driver

LED Specification

### INNLIGHTS INTEGRATION

Special Construction & Installation

Framework Design

Digital Signage Advising & Creating

Digital Signage via Online Remote

Monitoring Solutions

Permissions Support

### OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	140 / 120
REFRESH RATE [Hz]	2.000
IC DRIVER	Macroblock MBI
SCAN MODE	1 / 5
LED TYPE	SMD 4540
LED CHIP	Epistar (R) / Silan (G,B)
LED ENCAPSULATION	U - LED
GREY LEVEL [bit]	16
VIDEO PROCESSING	Novastar

### POWER SUPPLY

INPUT VOLTAGE [V]	110 - 240
WATTAGE MAX./AVG. [W /m <sup>2</sup> ]	600 / 210

### ENVIRONMENT

OPERATION HUMIDITY [RH]	10% - 90%
WORKING TEMP. MIN./MAX. [°C]	-20 / +50

SALES