



Innlights^{TC}

Rent & Buy LED Displays

InnScreen F8

[PIXEL PITCH 8,33 mm] Outdoor
 // Fixed-Installation Outdoor

All weather & UV resistance
 combined with high brightness.

Sealed cabinet design and full front access
 precisely define the F-Series as the prime
 selection for permanent outdoor installations.

2 cabinet sizes.



FACTS [m²]

BRIGHTNESS [cd/m ²]	6.000
WEIGHT [kg/m ²]	23 - 33
RESOLUTION [pixel/m ²]	120 x 120
WATTAGE MAX./AVG. [W/m ²]	742 / 248

SALES



Innlights^{TC}

Rent & Buy LED Displays

InnScreen F8 // Customized

PHYSICAL FACTS

PIXEL PITCH [mm]	8,33
BRIGHTNESS [cd/m ²]	6.000
PROTECTION LEVEL [Front/Back]	IP 65 / IP 54
CABINET MATERIAL	Aluminum sheet

CABINET SIZE [mm]	800 x 800 x 85
CABINET RESOLUTION [px]	96 x 96
CABINET WEIGHT [kg]	18

CABINET SIZE [mm]	1.200 x 1.200 x 85
CABINET RESOLUTION [px]	144 x 144
CABINET WEIGHT [kg]	40

INNLIGHTS CUSTOMIZED

IC Driver

LED Specification

INNLIGHTS INTEGRATION

Special Construction & Installation

Framework Design

Digital Signage Advising & Creating

Digital Signage via Online Remote

Monitoring Solutions

Permissions Support

OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	140 / 120
REFRESH RATE [Hz]	2.000
IC DRIVER	Macroblock MBI
SCAN MODE	1 / 3
LED TYPE	SMD 4540
LED CHIP	Epistar (R) / Silan (G,B)
LED ENCAPSULATION	U - LED
GREY LEVEL [bit]	16
VIDEO PROCESSING	Novastar

POWER SUPPLY

INPUT VOLTAGE [V]	110 - 240
WATTAGE MAX./AVG. [W /m ²]	600 / 210

ENVIRONMENT

OPERATION HUMIDITY [RH]	10% - 90%
WORKING TEMP. MIN./MAX. [°C]	-20 / +50

SALES